Materials Science and Engineering



The Origin of Phase Separation

- Self assembly of nanometersized features is one of the critical processes necessary to control in order to make devices for optoelectronic and quantum computing applications a reality.
- We examine the initiation mechanisms and self assembly of phase separated regions in compound semiconductors, which develop by both morphological (Fig. 1) and compositional (Fig. 2) variations. These features develop a lateral correlation length as the thickness increases that is equal to the modulation wavelength observed using TEM.
- Submitted to Physical Review Letters




Figure 1: Scanning Tunneling Micrograph (STM) of an InAs terminated multilayer with In-rich islands decorating the surface. Here the composition modulation develops as a result of a morphological variation




Figure 2: STM GaAs-terminated multilayer. The mesas have various reconstructions present, suggesting a variation in the composition within the layer

Mirecki Millunchick

DMR-9973352



Diversity in the Mirecki Millunchick Research Group



- From top left: Grant Martin (undergrad), Trey Sears (grad), Reggie Quinn (grad), Assistant Professor Chris Pearson, Alex Riposan (grad)
- From bottom left: Assistant Professor Joanna Mirecki
 Millunchick, Benny Perez Rodriguez (grad), Zhimei Zhu (grad),
 Jenny Lee (grad), Dr. Catalina Dorin (post doc)